



Wobblelight®



Wobblelight LED V3

The all new Wobblelight® LED V3, has the same great patented, self-righting technology with a new look. Still ideal for applications requiring temporary high output lighting for areas up to 75 feet diameter. This new look features an integrated carry handle into the body, LED panel technology and an integrated cord to give the unit a suitable for wet locations rating.

- Patented Self-Righting Technology
- 360° Lighting
- LED Panel Technology
- Integrated Power Cord
- Integrated Carry Handle
- IP55 Rated



Model No.	Lumens	Lighting Range	Bulb Type	Lamp Life	Kelvins	Watts	Amp Draw	Voltage	Temp Rated	Tested	Cord Type	IP Rating	Weight
111303LED	15,000	75 ft.	LED	50,000	5,000	185	1.8	120V	-40°F - 125°F	cUL	16/3 SJOOW	IP55	31 lbs



The patented self-righting Wobblelight® is ideal for applications requiring temporary high-output lighting in areas from 15 to 75 feet diameter. Bright and dependable, the Wobblelight® delivers maximum light output in a highly durable and portable package with no hot surfaces.

Replacement Bulbs:



500W Halogen
Model No. 111904



175W/400W Metal Halide
Model No. 111901/111903



All Wobblelight® models engineered with our patented self-righting design

- Patented Self-Righting Technology
- 360° Lighting
- No Hot Surfaces
- Interlink units together
- Durable

Model No.	Lumens	Lighting Range	Bulb Type	Lamp Life	Kelvins	Watts	Amp Draw	Linking Units	Voltage	Temp Rated	Tested	Cord Type	Weight
111302	8,000	25 ft.	Halogen	2,000	4,000	500	4.5	2	120V	-22°F	cUL	Not Included	28 lbs
111102	15,000	45 ft.	Metal Halide	10,000	4,000	175	1.9	5	120V	-22°F	cUL	Not Included	29 lbs
111104	40,000	75 ft.	Metal Halide	20,000	4,000	400	4	3	120V	-22°F	cUL	Not Included	33 lbs

Wobblelight Jr.® 27"



Replacement Bulbs:



85 Watt Fluorescent Bulb
Model No. 111908



80 Watt LED Bulb
Model No. 111980JR

- Patented Self-Righting Technology
- 360° Lighting
- No Hot Surfaces
- 5' Integrated Power Cord
- Durable

Model No.	Lumens	Lighting Range	Bulb Type	Lamp Life	Kelvins	Watts	Amp Draw	Voltage	Temp Rated	Tested	Cord Type	Weight
111203	5,000	25 ft.	Fluorescent	8,000	2,700	85	.6	120V	-20°F - 120°F	cUL	18/2 SJTW	13.5 lbs
111206	9,000	35 ft.	LED	35,000	5,000	80	.7	120V	-40°F - 125°F	cUL	18/2 SJTW	13.9 lbs