



## Features

- 3000K color temperature
- Excellent color rendering (92+ CRI)
- 12V DC constant current operation
- Small compact size for focused light
- Easy to install with spring steel mounting tabs
- Dimmable with TRIAC/CL/ELV dimmers
- Suitable for indoor dry locations
- 35,000 hours rated life

## Available Finishes



White



Satin Aluminum

## Dimming Options

- 15-100% TRIAC / CL / ELV

## Listing / Ratings

- Dry Location


## RMS Mini Series - 12V

Low-voltage, mini-recessed LED spotlights provide focused light that is useful in a variety of applications including: in-cabinet lighting, retail spaces, or built-ins. Available in 3 different models featuring fixed or adjustable lens options in either a white or satin aluminum finish

## Technical Information

Series	RMS12-30
Input Voltage	12V DC
CCT	3000K
CRI	92+
Wattage	1.75W / 3.2W
Lumens	84lm / 156lm
Beam Angle	15° swivel (501, 503 & 703) / 30° beam angle
Max Run	Dependent upon capacity of driver
Dimmable	15-100% TRIAC / CL / ELV
Mounting	Recessed mount
Rating	Dry location
Rated Life	35,000 hrs

## Primary Side Dimming Set-up



Standard Dimmer

+

Adaptive LED Driver  
(30W)

+



RMS Mini Series

RMS Mini Series - 12V

TRULUX LIGHTING SYSTEMS  
**RMS MINI SERIES**  
 SWIVELS & SPOTS  
 DOWNLIGHTING  
 LINEAR LIGHTING  
 ARCHITECTURAL LIGHTING  
 POWER SUPPLIES



RMS 401 Swivel  
 1.75W / 84Lm  
**RMS12-30-401-WH** (White)



RMS 401 Swivel  
 1.75W / 84Lm  
**RMS12-30-401-SA** (Satin Aluminum)



Mini LED 501 Swivel  
 1.75W / 84Lm  
**RMS12-30-501-WH** (White)  
**RMS12-30-501-SA** (Satin Aluminum)



Mini LED 503 Swivel  
 3.2W / 156Lm  
**RMS12-30-503-WH** (White)  
**RMS12-30-503-SA** (Satin Aluminum)



Mini LED 703 Swivel  
 3.2W / 156Lm  
**RMS12-30-703-WH** (White)



Mini LED 703 Swivel  
 3.2W / 156Lm  
**RMS12-30-703-SA** (Satin Aluminum)

RMS12 Mini Recessed Series include attached conkit with 22AWG bare wire leads