

LED performance in an economical 2x2 troffer.

Color: White

Weight: 5.2 lbs

<b>Project:</b>	<b>Type:</b>
<b>Prepared By:</b>	<b>Date:</b>

Driver Info		LED Info	
Type	Constant Current	Watts	30W
120V	0.24A	Color Temp	5000K (Cool)
208V	0.15A	Color Accuracy	81 CRI
240V	0.13A	L70 Lifespan	50,000
277V	0.11A	Lumens	2,904
Input Watts	27.00W	Efficacy	107.6 LPW
Efficiency	N/A		

## Technical Specifications

### Listings

#### UL Listed:

Suitable for damp locations

#### CCEA Compliant:

Luminaire Requirements used in Environmental Air Space per the electrical code specification of the City of Chicago

#### IESNA LM-70 & LM-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

#### DLC Listed:

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. DLC Product Code: P2VEHTP6

### Construction

#### IC Rated:

Suitable for direct contact with insulation

#### Ambient Operating Temperature:

-20°C (-4°F) to 40°C (104°F)

#### Lens:

Frosted Polystyrene

#### Housing:

Plastic frame & galvanized steel back housing

#### Finish:

White

#### Mounting:

Recessed into T-grid ceiling. Surface and recessed mounting kits available for drywall ceilings.

#### Green Technology:

Mercury and UV free. RoHS-compliant components.

### LED Characteristics

#### LEDs:

Long-life, high-efficiency, surface-mount LEDs

#### Lifespan:

50,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations

### Electrical

#### Driver:

Constant Current, Class 2, 120-277V, 50/60 Hz, 2kV surge protection, 120V: 0.24A, 208V: 0.15A, 240V: 0.13A, 277V: 0.11A

#### THD:

10.07% at 120V, 12.17% at 277V

#### Power Factor:

98.8% at 120V, 93.6% at 277V

#### Dimming:

0-10V, standard down to 10%

#### Note:

All values are typical (tolerance +/- 10%)

### Other


#### 5 Yr Limited Warranty:

The RAB 5-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

#### Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

## Dimensions



## Features

- Integrated 0-10V dimming
- 50,000-Hour LED lifespan
- 5-year, limited warranty
- 4 per case, must order in case quantity increments

## Ordering Matrix

Family	Housing Size	Wattage	Color Temp/CCT	Voltage	Lightcloud
T34	2X2	30		/D10	
	2X2 = 2' X 2' 2X4 = 2' X 4'	30 = 30W (2X2) 40 = 40W (2X4)	Blank = 5000K N = 4000K	/D10 = 0-10V Dimming	Blank = No Options /LC = Lightcloud® Control

Must order in case quantity increments. See product spec sheet for exact increments.