



Energetic Lighting's E1CPC series LED commercial low-profile canopy fixture provides a quick and versatile solution for hallways, garages, overhangs, gas stations, and other outdoor applications. The low-profile height allows for efficient packaging and unobtrusive surface installation. With input wattages of 44W and 65W, this fixture is designed to replace traditional 70W to 150W PSMH equivalent canopy fixtures. Fully sealed construction allows for wet location installation where direct contact with water is necessary. Light output is dimmable through standard 0-10v system control leads. Constructed of heavy duty cast aluminum with an integrated thermally efficient heatsink profile, each fixture is rated for a minimum L70 of 50,000 hours.

### Features

- Optional Microwave occupancy sensor
- Small footprint design
- 0-10v dimming
- Suitable for Wet Location use
- Easy tip in installation, and security lock bolt included
- Lightweight and compact profile

### Applications

- Commercial locations
- Warehouse
- Overhead task lighting
- General lighting

### Specification

<b>Order Number</b>	<b>83007</b>	<b>83008</b>
<b>Model Number</b>	<b>E1CPC40-750</b>	<b>E1CPC60-750</b>
<b>Body Color/Finish</b>		
<b>Beam Angle</b>	<b>110°</b>	<b>110°</b>
<b>Lumen Output</b>	<b>6091 LM</b>	<b>8948 LM</b>
<b>Luminous Efficacy</b>	<b>138 LM/W</b>	<b>138 LM/W</b>
<b>Input Power</b>	<b>44 W</b>	<b>65 W</b>
<b>Input Voltage</b>	<b>120-277 Vac</b>	<b>120-277 Vac</b>
<b>Power Factor</b>	<b>0.9</b>	<b>0.9</b>
<b>THD</b>	<b>0.15</b>	<b>0.15</b>
<b>Color Temp (CCT)</b>	<b>5000 K</b>	<b>5000 K</b>
<b>Color Rend (CRI)</b>	<b>70</b>	<b>70</b>
<b>Lifetime Rating</b>	<b>50000 hours</b>	<b>50000 hours</b>
<b>Warranty</b>	<b>5 Years</b>	<b>5 Years</b>
<b>Dimmability</b>	<b>0-10v</b>	<b>0-10v</b>
<b>Operating Temp</b>	<b>-40 to 104 (°F)</b>	<b>-40 to 104 (°F)</b>
<b>Environment</b>	<b>Wet Location</b>	<b>Wet Location</b>
<b>DLC</b>	<b>DLC Premium</b>	<b>DLC Premium</b>
<b>Safety Cert</b>	<b>ETL</b>	<b>ETL</b>
<b>Weight</b>	<b>6 LBS</b>	<b>6 LBS</b>
<b>Dimensions</b>	<b>9.0"x9.0"x3.6"</b>	<b>9.0"x9.0"x3.6"</b>