

CONSTANT VOLTAGE DRIVERS


NON-DIMMING

12V DC AND 24V DC HARDWARE



LED-DR-12 or LED-DR-24 (Class 2 hardwire driver)

6-1/4"L x 1-1/4"W x 1-13/16"H
Constant voltage, 12V or 24V DC, 1-25 watts
Use with 14AWG (min) supply wire,
copper conductors only, c/UR/us Recognized



LED-DR60-12 or LED-DR60-24 (Class 2 hardwire driver)

7-13/16"L x 1-3/4"W x 1-5/8"H
Constant voltage, 12V or 24V DC, 1-60 watts
Use with 14AWG (min) supply wire, copper conductors only
c/UR/us Recognized
Enclosure (ENCL-11) sold separately, 11-1/2"L x 1-7/8"W x 1-3/4"H



LED-DR100-12 or LED-DR100-24 (hardwire driver)

9"L x 2-9/16"W x 1-5/8"H
Constant voltage, 12V or 24V DC, 1-100 watts
15" 3C 18AWG input leads
15" 2C 16AWG output leads
Use with 14AWG (min) supply wire, copper conductors only
c/UR/us Recognized



12V DC PLUG-IN



PS-18-12VPI (plug-in power supply)

3-1/4"L x 1-7/8"W x 1"H
Constant voltage, 12V DC, 1-18 watts
6 foot 18AWG lead wire with DC jack, 6 foot 18AWG power cord with
2-prong polarized plug, c/UL/us Listed



PS-36-12VPI (plug-in power supply)

4-3/4"L x 2-5/16"W x 1-1/2"H
Constant voltage, 12V DC, 1-36 watts
5 foot 18AWG lead wire with DC jack, 6 foot 18AWG power cord with
3-prong grounded plug, c/UL/us Listed



PS-60-12VPI (plug-in power supply)

4-3/4"L x 2-5/16"W x 1-1/2"H
Constant voltage, 12V DC, 1-60 watts
5 foot 18AWG lead wire with DC jack, 6 foot 18AWG power cord with
3-prong grounded plug, c/UL/us Listed



PS-96-12VPI (plug-in power supply)

6-3/4"L x 2-3/4"W x 1-5/8"H
Constant voltage, 12V DC, 1-96 watts
5.5 foot 18AWG lead wire with DC jack, 5.5 foot 18AWG power cord with
3-prong grounded plug, c/UL/us Listed



DIMMING



PS-25-12, PS-25-24

4"L x 3-7/8"W x 1-7/16"H
 88-264 VAC input, 12V or 24V DC output
 1-25 watts, single output terminal
 Can load up to 100% (no minimum load)
 Overload/overvoltage/short circuit protection
 Two year warranty, c/UR/us Recognized



PS-60-12, PS-60-24

6-1/4"L x 3-7/8"W x 1-1/2"H
 88-264 VAC input, 12V or 24V DC output
 1-60 watts, single output terminal
 Can load up to 100% (no minimum load)
 Overload/overvoltage/short circuit protection
 Two year warranty, c/UR/us Recognized



PS-100-12, PS-100-24

7-7/8"L x 3-7/8"W x 1-1/2"H
 88-264 VAC input, 12V or 24V DC output
 1-100 watts, double output terminals
 Can load up to 100% (no minimum load)
 Overload/overvoltage/short circuit protection
 Two year warranty, c/UR/us Recognized



PS-150-12, PS-150-24

7-7/8"L x 4-7/8"W x 2"H
 88-264 VAC input, 12V or 24V DC output
 1-100 watts, double output terminals
 Can load up to 100% (no minimum load)
 Overload/overvoltage/short circuit protection
 Two year warranty, c/UR/us Recognized

PWM DIMMER AND REPEATER

For instructions and FAQs regarding PWM dimming, visit www.americanlighting.com.



AL-PWM-6A

Slide dimmer with on/off switch, White
 Fits decora style trim plates and standard
 junction boxes; 12-24V DC input only
 6A load maximum, PWM (pulse width
 modulation) technology eliminates
 voltage surges and AC flicker
 One year warranty



AL-3R-6A

5"L x 2-1/2"W x 1-1/16"H
 Repeater for use with AL-PWM dimmer and PS
 Series drivers, 12-24 V DC input only, 3 x 6A load
 maximum Two power inputs and one signal output
 One year warranty



H

